




LED Balloon Light System & Accessories





The **Yuang Light** LED Balloon Light System is suited to a wide range of industrial, construction and outdoor uses. The system has been developed for ease of use and maximum portability, and our LED technology ensures that our lights are bright enough for any application and have long life spans while at the same time minimizing power consumption.

Through our cutting-edge inhouse R&D and manufacturing capabilities, we develop energy-saving and environmentally-friendly products. Yuang Light is the first balloon light manufacturer in Asia to receive major international certifications such as CE, PSE, RCM and ETL.

Yuang Light takes our corporate social responsibility seriously, our workplace meets the ISO 9001 standard and received a D-U-N-S® certification. Yuang Light has developed green products for markets in Europe, Asia and Oceania. We provide our international agents with comprehensive education and training tailored to local conditions. Our partners, ranging from police and fire departments, to the military and local governments, demand efficient communication, as well as products of the highest quality.



ISO
9001:2015
CERTIFIED





LED Balloon Light System

Brighten Up Your Night.



Life Span > 50,000 hrs

Energy-efficient with service life of more than 50,000 hours.



IP65

LED panels are dust-tight, water-resistant, and flameproof.



Family Friendly

RoHS certified recyclable materials are kinder to human health and the environment.



Glare-Free 360° Illumination

Diffused, glare and double-imaging-free illumination.



Smart Control

APP controlled functionality like dimming and RGB mood lighting.



Low-Maintenance

Complete ecosystem for easy part replacement.



Lightweight & Portable

Easy transportation in the durable, 600 denier nylon carry bag provided.



Easy Setup

Flexible mounting on tripods, ceilings, vehicles, construction equipment and more.



Sturdy & Safe

Patented safety chain ensures safe and stable tripod operation.



Customizable

Customizable light covers to show your brand logo.



Versatile Usage

Suitable for construction, events, traffic control, disaster relief, filming, and more.



Support

Our technical consultants can help evaluate and simulate your illumination needs.



Quality Guaranteed

Made in Taiwan, your trusted partners in OEM and ODM.




LED Balloon Light


Illumination

Data for reference only,
actual values may differ.


TINY LED Balloon Light



MINI LED Balloon Light
100 / 200 W



MIDI LED Balloon Light



MAXI LED Balloon Light
500 / 960 W



LED Balloon Light Series

TINY	50W	RGBW	(AC/DC)
MINI	100W	200W	
MIDI	300W		
MAXI	500W	960W	




TINY LED Balloon Light

50 W RGBW AC / DC

Our 50 W TINY LED Balloon Lights are the most compact and portable in our collection and available in white or RGBW, and AC or DC. While these family friendly lights aren't as powerful as their bigger cousins, they emit more than enough for everyday activities. And since they are dimmable, you can always set them to just the right brightness, whether you're cooking, reading, dining or just enjoying the great outdoors.

DIMENSIONS



TECHNICAL DATA

50 W RGBW

General	Voltage	AC 100-240 V / DC 29 V
	Operating Time	4-5 hrs
	Operating Amperage	AC 0.97 A / DC 1.72 A
	Power Consumption (±5%)	AC 55 W / DC 50 W
Lamp	Lamp+Tripod	4.9 kg
	Panel Power Consumption (±5%)	45 W 50 W / 40 W RGBW
	Panel Luminous Flux (±10%)	6,800 lm 50 W / 6,500 lm RGBW
	Correlated Color Temperature	5,000 K
	Width	500 mm
Tripod	Height	320 mm
	Weight	2.3 kg
	Height (min-max)	825-1600 mm
	Weight	2.6 kg
	Collapsed Height	770 mm
Battery (DC model)	Collapsed Width	120 mm
	Cell	Panasonic NCR18650PF
	Dimension	94 x 72.6 x 199 mm
	Weight	1.78 (±0.05 kg)
	IP rating	IP 55
	Certification	PSE, UN38.3

ACCESSORIES

The TINY LED Balloon Light standard package includes:

- LED Light System
- Omni Light Cover
- X Small Tripod
- Light Carry Bag
- X Small Tripod Carry Bag
- Battery (DC Model)



LIGHT CARRY BAG



X SMALL TRIPOD
(See page 32)



BATTERY
(DC model)




X SMALL TRIPOD CARRY BAG



INFINITE RGB COLORS VIA APP (RGBW model)

LIGHTING DATA



CUSTOMIZATION

Our TINY LED Balloon Light can also be customized with:


- Trolley Mount
- Light Cover
- Fog Light
- Timer
- Custom Color Temperature
- Dimmer
- Remote Control / APP

MINI LED Balloon Light

100 W 200 W

Our MINI LED Balloon Lights emit bright, diffused light that is suitable for indoor spaces and outdoor events. Released in 100 W and 200 W versions, they can be used to light up film sets, provide even lighting for studio photography and interior construction, and general portable lighting for outdoor activities like camping, sporting events and parties. They come with a sturdy carry bag or an optional balloon light crate that is stackable, prevents rolling when transporting and with customizable interior partitioning.

DIMENSIONS



TECHNICAL DATA

100 W

200 W

General	Voltage	AC 100-240 V	AC 100-240 V
	Frequency	50/60 Hz	50/60 Hz
	Operating Amperage	1.2 A	2.3 A
	Power Consumption (±5%)	110 W	210 W
	Lamp+Tripod	8.2 kg	8.4 kg
Lamp	Panel Power Consumption (±5%)	90 W	180 W
	Panel Luminous Flux (±10%)	15,600 lm	28,000 lm
	Correlated Color Temperature	5,000 K	5,000 K
	Width	600 mm	600 mm
	Height	435 mm	435 mm
Tripod	Weight	5 kg	5.2 kg
	Height (min-max)	1050-2035 mm	1050-2035 mm
	Weight	3.2 kg	3.2 kg
	Collapsed Height	930 mm	930 mm
	Collapsed Width	120 mm	120 mm

ACCESSORIES

The MINI LED Balloon Light standard package includes:

- LED Light System
- Omni Light Cover
- Small Tripod
- Light Carry Bag
- Small Tripod Carry Bag

Optional: Stackable Protective Crate.



LIGHT CARRY BAG




SMALL TRIPOD
(See page 32)



SMALL TRIPOD CARRY BAG

LIGHTING DATA



CUSTOMIZATION

Our MINI LED Balloon Light can also be customized with:


- Trolley Mount
- Light Cover
- RGB Light
- Fog Light
- Timer
- Custom Color Temperature
- Dimmer
- Remote Control / APP

MIDI LED Balloon Light

300 W

Our MIDI LED Balloon Lights emit light that is close to sunlight. They are best for situations where no-nonsense lighting is essential for safety and practicality. They can be used for rescue operations, tunneling, oil and gas exploration, outdoor construction and on large film sets.

DIMENSIONS



TECHNICAL DATA

300 W

General	Voltage	AC 100-240 V
	Frequency	50/60 Hz
	Operating Amperage	1.5 A/3.1 A
	Power Consumption (±5%)	150 W/300 W
	Lamp+Tripod	15.8 kg
Lamp	Panel Power Consumption (±5%)	130 W/260 W
	Panel Luminous Flux (±10%)	25,000 lm/50,000 lm
	Correlated Color Temperature	5,000 K
	Width	820 mm
	Height	630 mm
Tripod	Weight	8.4 kg
	Height (min-max)	1450-2180 mm
	Weight	7.4 kg
	Collapsed Height	1340 mm
	Collapsed Width	180 mm

ACCESSORIES

The MIDI LED Balloon Light standard package includes:

- LED Light System
- Omni Light Cover
- Medium Tripod
- Light Carry Bag
- Medium Tripod Carry Bag



LIGHT CARRY BAG




MEDIUM TRIPOD
(See page 32)



MEDIUM TRIPOD CARRY BAG

LIGHTING DATA



CUSTOMIZATION

Our MIDI LED Balloon Light can also be customized with:

- Trolley Mount
- Light Cover
- RGB Light
- Fog Light
- Timer
- Custom Color Temperature
- Dimmer
- Remote Control / APP




MAXI LED Balloon Light

500 W 960 W

Our MAXI LED Balloon Lights are the brightest in our collection and come in 500 W and 960 W versions. Their wide coverage make them essential for large-scale infrastructure projects like roadworks and construction projects, and they provide ample lighting at sporting events. Their easy setup and portability make them invaluable in fire-fighting and other disaster relief situations.

DIMENSIONS



TECHNICAL DATA

500 W

960 W

General	Voltage	AC 100-240 V	AC 100-240 V
	Frequency	50/60 Hz	50/60 Hz
	Operating Amperage	2.9 A/5.5 A	5.3 A/10.6 A
	Power Consumption (±5%)	245 W/490 W	485 W/970 W
	Lamp+Tripod	31.5 kg	36.5 kg
Lamp	Panel Power Consumption (±5%)	216 W/432 W	432 W/864 W
	Panel Luminous Flux (±10%)	36,000 lm/72,000 lm	72,000 lm/145,000 lm
	Correlated Color Temperature	5,000 K	5,000 K
	Width	910 mm	910 mm
	Height	700 mm	700 mm
Tripod	Weight	14.5 kg	19.5 kg
	Height (min-max)	1740-3700 mm	1740-3700 mm
	Weight	17 kg	17 kg
	Collapsed Height	1980 mm	1980 mm
	Collapsed Width	210 mm	210 mm

ACCESSORIES

The MAXI LED Balloon Light standard package includes:

- LED Light System
- Omni Light Cover
- Large Tripod
- Light Carry Bag
- Large Tripod Carry Bag



LIGHT CARRY BAG




LARGE TRIPOD
(See page 32)



LARGE TRIPOD CARRY BAG

LIGHTING DATA



CUSTOMIZATION

Our MAXI LED Balloon Light can also be customized with:

- Trolley Mount
- Light Cover
- RGB Light
- Fog Light
- Timer
- Custom Color Temperature
- Dimmer
- Remote Control / APP

LED Balloon Light Series

CE CERTIFICATION

GENERAL

- Voltage
- Frequency
- Operating Amperage

LAMP

- Power Consumption (±5%)
- Panel Power Consumption (±5%)
- Average Lamp Life
- Color Rendering Index
- Correlated Color Temperature
- Luminous Flux (±10%)
- Width
- Height
- Weight

TRIPOD

- Height (min-max)
- Collapsed Height
- Collapsed Width
- Weight

TROLLEY

- Height
- Length
- Width
- Weight

WEIGHT

- Lamp + Tripod
- Lamp + Trolley

BATTERY (50W DC model)

- Cell
- Dimension
- Weight
- IP rating
- Certification
- Operating Time



TINY

50 W

RGBW



MINI

100 W

200 W



MIDI

300 W



MAXI

500 W

960 W

AC 100-240 V / DC 29 V	AC 100-240 V	AC 100-240 V	AC 100-240 V	AC 100-240 V	AC 100-240 V
50/60 Hz	50/60 Hz	50/60 Hz	50/60 Hz	50/60 Hz	50/60 Hz
AC 0.97 A / DC 1.72 A	1.2 A	2.3 A	1.5 A/3.1 A	2.9 A/5.5 A	5.3 A/10.6 A
AC 55 W / DC 50W	110 W	210 W	150 W (half) / 300 W (full)	245 W (half) / 490 W (full)	485 W (half) / 970 W (full)
45 W 50 W / 40 W RGBW	90 W	180 W	130 W (half) / 260 W (full)	216 W (half) / 432 W (full)	432W (half) / 864 W (full)
> 50,000 hrs	> 50,000 hrs	> 50,000 hrs	> 50,000 hrs	> 50,000 hrs	> 50,000 hrs
80	80	80	80	80	80
5,000 K	5,000 K	5,000 K	5,000 K	5,000 K	5,000 K
6,800 lm 50 W / 6,500 lm RGBW	15,600 lm	28,000 lm	25,000 lm (half) / 50,000 lm (full)	36,000 lm (half) / 72,000 lm (full)	72,000 lm (half) / 145,000 lm (full)
500 mm	600 mm	600 mm	820 mm	910 mm	910 mm
320 mm	435 mm	435 mm	630 mm	700 mm	700 mm
2.3 kg	5 kg	5.2 kg	8.4 kg	14.5 kg	19.5 kg
825-1600 mm	1050-2035 mm	1050-2035 mm	1450-2180 mm	1740-3700 mm	1740-3700 mm
770 mm	930 mm	930 mm	1340 mm	1980 mm	1980 mm
120 mm	120 mm	120 mm	180 mm	210 mm	210 mm
2.6 kg	3.2 kg	3.2 kg	7.4 kg	17 kg	17 kg
1030 mm	1030 mm	1030 mm	1560 mm	1755 mm	1755 mm
720 mm	720 mm	720 mm	1075 mm	1360 mm	1360 mm
460 mm	460 mm	460 mm	750 mm	1515 mm	1515 mm
12.8 kg	12.8 kg	12.8 kg	24.6 kg	135 kg	135 kg
4.9 kg	8.2 kg	8.4 kg	15.8 kg	31.5 kg	36.5 kg
15.1 kg	17.8 kg	18 kg	33.0 kg	149.5 kg	154.5 kg
Panasonic NCR18650PF					
94 x 72.6 x 199 mm					
1.78±0.05 kg					
IP 55					
PSE, UN38.3					
4-5 hours					

Dimensions tolerance: ±10 mm
As part of our continuous efforts to improve our products, features and specifications may change without notice.

LED Balloon Light System

ETL
CERTIFICATION



TINY

50 W



MINI

100 W

200 W



MIDI

300 W



MAXI

500 W

900 W

GENERAL	
Voltage	AC 100-240 V
Frequency	50/60 Hz
Operating Amperage	0.6 A
LAMP	
Power Consumption (±5%)	60 W
Panel Power Consumption (±5%)	55 W
Average Lamp Life	> 50,000 hrs
Color Rendering Index	80
Correlated Color Temperature	5,000 K
Luminous Flux (±10%)	7,200 lm
Width	500 mm
Height	320 mm
Weight	3 kg
TRIPOD	
Height (min-max)	825-1600 mm
Collapsed Height	770 mm
Collapsed Width	120 mm
Weight	2.6 kg
TROLLEY	
Height	1030 mm
Length	720 mm
Width	460 mm
Weight	12.8 kg
WEIGHT	
Lamp + Tripod	5.6 kg
Lamp + Trolley	15.8 kg

AC 100-240 V	AC 100-240 V	AC 100-240 V	AC 100-240 V	AC 100-240 V	AC 100-240 V
50/60 Hz	50/60 Hz	50/60 Hz	50/60 Hz	50/60 Hz	50/60 Hz
0.6 A	1.2 A	2.3 A	1.9 A/3.5 A	2.9 A/5.5 A	5.0 A/9.9 A
60 W	110 W	210 W	155 W (half) / 310 W (full)	255 W (half) / 510 W (full)	455 W (half) / 910 W (full)
55 W	90 W	180 W	130 W (half) / 270 W (full)	216 W (half) / 432 W (full)	402W (half) / 804 W (full)
> 50,000 hrs	> 50,000 hrs	> 50,000 hrs	> 50,000 hrs	> 50,000 hrs	> 50,000 hrs
80	80	80	80	80	80
5,000 K	5,000 K	5,000 K	5,000 K	5,000 K	5,000 K
7,200 lm	13,200 lm	25,200 lm	18,600 lm (half) / 37,200 lm (full)	30,600 lm (half) / 61,200 lm (full)	55,000 lm (half) / 110,000 lm (full)
500 mm	600 mm	600 mm	820 mm	910 mm	910 mm
320 mm	435 mm	435 mm	630 mm	700 mm	700 mm
3 kg	5 kg	5.2 kg	8.5 kg	14.5 kg	19.5 kg
825-1600 mm	1050-2035 mm	1050-2035 mm	1450-2180 mm	1740-3700 mm	1740-3700 mm
770 mm	930 mm	930 mm	1340 mm	1980 mm	1980 mm
120 mm	120 mm	120 mm	180 mm	210 mm	210 mm
2.6 kg	3.2 kg	3.2 kg	7.4 kg	17 kg	17 kg
1030 mm	1030 mm	1030 mm	1560 mm	1755 mm	1755 mm
720 mm	720 mm	720 mm	1075 mm	1360 mm	1360 mm
460 mm	460 mm	460 mm	750 mm	1515 mm	1515 mm
12.8 kg	12.8 kg	12.8 kg	24.6 kg	135 kg	135 kg
5.6 kg	8.2 kg	8.4 kg	15.9 kg	31.5 kg	36.5 kg
15.8 kg	17.8 kg	18 kg	33.1 kg	149.5 kg	154.5 kg

Dimensions tolerance: ±10 mm
As part of our continuous efforts to improve our products, features and specifications may change without notice.

Mobile Lighting Tower

System

SINGLE	250W
TWIN	500W
QUADRO	1200W



SINGLE TWIN


250 W

500 W

Our ultra bright Mobile Lighting Towers emit undiffused, directional light that is essential for construction. They are mobile and exceptionally easy to setup and operate. Their durability and reliability mean they will last on the roughest of sites, and as an added bonus are good for the environment.

- ULTRA BRIGHT
- LIGHTWEIGHT
- DIRECTIONAL
- IP 65
- STEEL MESH PROTECTOR
- LOW-POWER CONSUMPTION


DIMENSIONS



TECHNICAL DATA

		250 W	500 W
General	Voltage	AC 100-240 V	AC 100-240 V
	Frequency	50/60 Hz	50/60 Hz
	Operating Amperage	3 A	6 A
	Power Consumption (±5%)	250 W	500 W
Lamp	Average Lamp Life	> 50,000 hrs	> 50,000 hrs
	CRI	70	70
	CCT	5,000 K	5,000 K
	Luminous Flux (±10%)	42,000 lm	84,000 lm
Tripod	Width	360 mm	930 mm
	Height	420 mm	400 mm
	Weight	7.6 kg	12 kg
	Height (min-max)	1450-2180 mm	-
Trolley	Collapsed Height	1340 mm	-
	Collapsed Width	180 mm	-
	Weight	7.4 kg	-
	Height	-	1560 mm
	Length	-	1075 mm
	Width	-	750 mm
	Weight	-	24.6kg

LIGHTING DATA



QUADRO

1200 W

Our QUADRO Mobile Lighting Towers shine a straight-line of undiffused, directional light up to 35 meters. The lamp angles are freely adjustable, and the QUADRO can share a high wattage generator with your other equipment, perfect for large-scale construction projects.



ULTRA BRIGHT



DIRECTIONAL




IP 65



LOW-POWER
CONSUMPTION

DIMENSIONS



TECHNICAL DATA

1200 W

General	Voltage	AC 90-305 V
	Frequency	50/60 Hz
	Operating Amperage	10.9 A
	Power Consumption (±5%)	1200 W
Lamp	Average Lamp Life	> 50,000 hrs
	CRI	80
	CCT	5,000 K
	Luminous Flux (±10%)	208,000 lm
	Width	1092 mm
	Height	765mm
Trolley	Weight	55 kg
	Height	2050-5145 mm
	Length	1360 mm
	Width	1515 mm
	Weight	135 kg

LIGHTING DATA




1200 W	Distance	1 m	5 m	10 m
	Area	9 m ²	65 m ²	50 m ²
	Lux	760 lx	530 lx	170 lx



Accessories

LIGHT COVERS
TRIPODS
TROLLEYS



Accessories

LIGHT COVERS

OMNI REFLECTIVE

The covers for our LED Balloon Lights inflate into an elegant and efficient balloon shape with air from the fans. We offer two different standard covers; the Omni Light Cover and the Reflective Light Cover. Designed to be used with our LED Lighting Systems, they are easy to attach and hold their shape perfectly. Contact us for even more customization options.

- 

OMNI-DIRECTION/
REFLECTIVE
- 


WATERPROOF
- 

FLAMEPROOF
- 

PHENOLIC
YELLOWING RESISTANT
- 


WASHABLE

OMNI



- MINI 600 × 435 mm
- MIDI 820 × 630 mm
- MAXI 910 × 700 mm

REFLECTIVE



- MINI 600 × 435 mm
- MIDI 820 × 630 mm
- MAXI 910 × 700 mm

Our Omni Light Covers produce omni-directional, even lighting throughout a space. The covers are washable, easily replaced, waterproof, tear and flame-proof. They are ideal for situations that require true omni-directional illumination like photography and tunneling.

Our Reflective Light Covers reflect light down onto the ground, acting as highly efficient street lights. The covers are washable, easily replaced, waterproof and flameproof. They minimize light pollution and are ideal for roadworks and construction.

for
**LED
Balloon
Light
System**



Accessories

TRIPODS

- X SMALL
- SMALL
- MEDIUM
- LARGE

Our tripods are designed to integrate seamlessly into our lighting systems. Compact and reliable, they are a breeze to carry and collapse easily for storage. They can extend from a height of 1 meter to 4 meters. Safety features include a safety-chain to prevent accidental disconnection as well as a T-knob that can be tightened for extra safety. Tripods include a system for power cord storage and leg fasteners for safe transportation.

The color and structure of our tripods can be customized.

Dimension tolerance: ±10 mm

X SMALL

for TINY LED Balloon Light



Height (min-max)	825-1600 mm
Width	880 mm
Weight	2.6 kg
Collapsed Height	770 mm
Collapsed Width	120 mm

1

2

1

2


Cable Hook + Storage

Integrated Ruler

Safety Chain

SMALL

for MINI LED Balloon Light



Height (min-max)	1050-2035 mm
Width	880 mm
Weight	3.2 kg
Collapsed Height	930 mm
Collapsed Width	120 mm

1

2

1

2

Cable Hook + Storage

Integrated Ruler

Safety Chain

MEDIUM

for MIDI LED Balloon Light
SINGLE Mobile Lighting Tower



Height (min-max)	1450-2180 mm
Width	1110 mm
Weight	7.4 kg
Collapsed Height	1340 mm
Collapsed Width	180 mm

1

2

3

4

5

6

Anchor Holes

Articulated Feet


for

LED Balloon Light System

Mobile Lighting Tower System

LARGE

for MAXI LED Balloon Light



Height (min-max)	1740-3700 mm
Width	1500 mm
Weight	17 kg
Collapsed Height	1980 mm
Collapsed Width	210 mm

1

3

4

1

2

5

6

7

Cable Hook

Cable Hook + Storage

Maximum Height Red Mark

Safety Chain

Anchor Holes

Security T-Knob

Cable Velcro

Accessories

TROLLEYS

SMALL MEDIUM LARGE

Our trolleys are the perfect size to transport generators. Made from strong steel with four sturdy wheels, they are as mobile as they are robust. Packed full of safety features, our trolleys make moving equipment a breeze.

The color and structure of our trolleys can be customized.
Dimension tolerance: ±10 mm

for
LED Balloon Light System
Mobile Lighting Tower System





Brake Pedal



Adjustable Stabilizer Legs



Compartment



Telescopic Pole Crank



Telescopic Pole Safety Pin

LED Light Customization Possibilities

Our lights can be customized to allow their color to be adjusted across the **RGB** spectrum or converted to **fog lights**. In addition, a **timer** can set how many seconds different colors display. Lights can also be **customized to a specific color** for purposes like emergency or security lights. **Dimmers** controlled by manual or **remote control** switches can also be installed or use our latest **APP** for full control of your lights via smartphone.

The shape of our light covers can be customized, as can the color and structure of our trolleys and tripods.



Light color adjustable across the RGB spectrum.



Dim light manually or by remote control.



Switch between fog and white light.



Use remote to control timer, dimmer and turn lights on and off.



Set timer to change colors at intervals.




APP controlled functionality like dimming and RGB mood lighting.



Set correlated color temperature between 2500 K and 6500 K.



Solar panel connectivity.



TÜRKİYE YETKİLİ TEMSİLCİSİ VE DAİSTRİBÜTÖRÜ

aren kurtarma
ekipmanları

AREN KURTARMA EKİPMANLARI LTD. ŞTİ.
Bahçelievler Mah. Taşkent Cad.
No:47/B 06490 Çankaya, Ankara

Tel: 0312 9630696
E-Posta: destek@arenkurtarma.com
www.arenkurtarma.com



🌐 yuanglight.com
📍 5F, No. 210, Sec. 2, Zhonghua Road,
Tucheng District, 236 New Taipei City, Taiwan
☎ +886 2 2268 0546
📠 +886 2 2268 1907
✉ service@cyuang.com
📱 @yuanglight

